

Revolution Retail Systems

FORTIS™ SERIES



Fortis 4SE/5SE - 4LW/5LW





Fortis 4SE/5SE



Fortis 4LW/5LW

HARDWARE FEATURES:

- Closed Loop Architecture of Notes and Coins; No Manual Intervention Required
- Continuous 24/7 Monitoring
- Audit Cassette Allowing Automatic Internal Validation of Any Recycling Cassette
- Lockable Large-Capacity Deposit Cassette Accepting Up to 7,200 Notes
- “Fitness Sort” on Recycled Notes
- Two Roll Storages with Capacity Up to 250 Notes Each to Hold Escrow and Rejected Notes, Respectively
- Pocket Note Acceptor Handles Large Bundles of Notes (Up to 250 Notes)
- Flexible Note Orientation (No Need to Separate or Face Notes)
- Scalable – Cluster Format – Up to Two (2) Note Recyclers in Dual Configurations
- Coin Discrimination (i.e. Counterfeit Coin Rejection)
- Dispenses Coins Directly into Till Tray – Fortis 4SE & 5SE
- Dispenses Coins Directly into Till Drawer – Fortis 4LW & 5LW
- Coin Cup LEDs (Notification if Change is Left in Cups)
- Integrated Printer
- Optional Integrated Biometrics (Fingerprint Reader)
- Optional Integrated Barcode Scanner for Till Check In/Out
- Optional Integrated Drop/Storage Vault
- Uninterruptible Power Supply

SOFTWARE FEATURES:

- PCI Compliant
- REACH™ Remote Monitoring and Management
- Real Time Cash/Coin Level Monitoring
- Reporting – Standard or Custom
- Lane and/or Clerk Accountability
- Tills and Drop Bags Automatically Traced to a Specific User by Utilizing Bar-Coding
- Multiple Tills per Register/Lane
- Configurable User Permission Levels for Equipment Access
- Multiple User Authentication Schemes (Log-in and PIN, or Biometrics)
- Automatic Prompting of Periodic Password Changes
- Customized Programming of ID Cards
- Track Monies Outside of Unit with External Vault Fund Function
- Guided Deposit Preparation: Automatically Calculates and Moves Deposit to Courier Cassette
- Automatic End of Day Reporting
- Courier Specific Log-In Menu
- Video Troubleshooting Tips
- Video Guidance for System Operation


FEATURE CAPABILITY:

- Ability to Integrate with POS System
- Same Day Credit on Deposit (Provisional Credit)


SPECIFICATIONS

Physical Characteristics (nominal):	Fortis 4SE	Fortis 4LW	Fortis 5SE	Fortis 5LW
Height	60.24" (1,530.07 mm)	60.24" (1,530.07 mm)	60.24" (1,530.07 mm)	60.24" (1,530.07 mm)
Width	42.57" (1,081.39 mm)	51.58" (1,310.23 mm)	42.57" (1,081.39 mm)	51.58" (1,310.23 mm)
Depth (install depth)	39.57" (1,005.00 mm)	39.57" (1,005.00 mm)	39.57" (1,005.00 mm)	39.57" (1,005.00 mm)
Weight (empty)	2,150 lbs (975 kg)	2,250 lbs (1,021 kg)	2,150 lbs (975 kg)	2,250 lbs (1,021 kg)
Device Configuration:				
Number of Recycle Cassettes	4	4	3	3
Number of Small Recycle Cassettes	0	0	2	2
Number of Deposit Cassettes	1	1	1	1
Number of Audit Cassettes	1	1	1	1
Notes:				
Capacity per Cassette (approximate):				
Recycle Cassette	3,000 notes	3,000 notes	3,000 notes	2,700 notes
Small Cassette	800 notes	800 notes	800 notes	800 notes
Deposit Cassette	7,200 notes	7,200 notes	7,200 notes	7,200 notes
Roll Storages (total)	500 notes	500 notes	500 notes	500 notes
Total Capacity of Notes	19,200 notes	19,200 notes	17,800 notes	17,800 notes
Processing Speed In or Out (max)	10 notes/sec	10 notes/sec	10 notes/sec	10 notes/sec
Recycling Capability (max)	(4) denominations	(4) denominations	(5) denominations	(5) denominations
Coin:				
Number of Recycle Modules	4	4	4	4
Capacity by Denomination (maximum):				
• Nickels	3,000	6,500	3,000	6,500
• Dimes	6,200	15,000	6,200	15,000
• Quarters	2,700	5,800	2,700	5,800
• Loonies	1,800	2,050	1,800	2,050
• Toonies	1,700	1,900	1,700	1,900
• Sorted Overflow	---	15,000	---	15,000
Total Coin Capacity	15,400	46,250	15,400	46,250
Coin Processing Speed In (up to)	700 coin/min	3,000 coin/min	700 coin/min	3,000 coin/min
Coin processing Speed Out (up to)	16 coin/sec	32 coin/sec	16 coin/sec	32 coin/sec
Accepts Up To	(6) denominations	(6) denominations	(6) denominations	(6) denominations
Recycle Up To	(4) denominations	(4) denominations	(4) denominations	(4) denominations

FORTIS 4SE / FORTIS 5SE



FORTIS 4LW / FORTIS 5LW



- 1 SYSTEM MUST BE SECURED TO LEVEL FLOOR.
- 2 IF THE A/C OUTLET IS NOT LOCATED IN THE INDICATED AREA BEHIND THE UNIT, THIS DIMENSION TO BE A MINIMUM OF 3".
IF THE A/C OUTLET IS LOCATED IN THE INDICATED AREA BEHIND THE UNIT, THIS DIMENSION TO BE A MINIMUM OF 5".
- 3 IF UPS/AC DISTRIBUTION BOX POWER SWITCH IS ON THE LEFT SIDE OF THE MACHINE, THIS DIMENSION CAN BE MINIMUM 1.00 [25.4]
OTHERWISE THIS DIMENSION IS MINIMUM 6.00 [154.2].